

iVMS-5200 Pro Version 3.3.2 What's New

This document briefly introduces the new functions and features in the **iVMS-5200 Pro Version 3.3.2** updated from Version 3.2.302.

The content of this manual is furnished for informational use only and it is subject to change without notice.

Added

- Add the Remote Site Manager module for centralized management of CMSs.
- Add up to 5 CMSs to RSM via IP address or domain name.
- Add function modules (ANPR and Mobile Surveillance) to basic module for management.
- Support RSM user and role management.
- Automatically and manually synchronize the RSM users to corresponding CMSs.
- RSM user with specific permissions can access the CMS.
- Import domain user for RSM.
- Logs expiration date, IP address settings, NTP settings, and active directory are configurable for RSM.
- Check alarm information of the added CMSs when accessing RSM via Control Client by uploading CMS alarms to RSM.
- Arm or disarm the specific CMS when accessing RSM via Control Client.
- Logical alarm available for triggering the linkage actions of other function modules.
- Post-record period configurable for recording video from periods following detected events.
- Add NVR as Central Storage Server for data storage.
- Obtain the camera name and the recording schedule from device.
- Set the POS data expiry date.
- Configure the FTP server's parameters to enable the uploading of the video taken by the Mobile Client to the FTP server.
- Manually back up the database.
- Import function module's cameras to the video surveillance.
- Add permission items about checking logs and server health status.
- Connect to the decoding device.
- Support CVR N+1 hot spare function.
- Provide ANR function for CVR.
- Notify Control Client to synchronize with the system to get the latest resources.
- Add 16/32/64/128/256 and custom playback speed in Control Client.
- Captured event picture can be attached to notification email.

- Service Manager provides reason for registration failure.
- Provide normal and hot spare (form a 1+1 hot spare system consisting of a host CMS and a spare CMS) installation mode
- Support GPU decoding for live view and playback.
- Optimized fisheye expansion mode.
- Provide Video Wall Client Software
 - Support language switch.
 - Load cameras of function modules.
 - View live video and playback of function modules' cameras.
 - Get function modules' cameras' stream through Stream Media Server.
 - Display video of function modules' cameras on video wall.
 - Support displaying the video the device connected via HiDDNS.
 - Play back videos stored on the NVR.
 - One default video wall is available and no more video walls can be added.
 - Display logical alarm on the video wall.
 - Optimize the displaying of alarm on video wall.
 - Display the live view and the playback of the third-party camera on the video wall.
- Support the live view and the playback of the added function modules' cameras via Mobile Client.

Updated:

- Separate some basic functions from video surveillance to form the basic module used for integrating the function modules and providing general functions.
- Set password for system for the first time to login.
- Set the linkage actions for the detected events and the event can also be saved as alarm.
- Check alarm information, alarm and event logs via Control Client.
- Trigger the resources of other areas for linkage actions.
- Optimize the display of device health status.
- Optimize system License for enhancing the system security.
- Optimize License activation method by providing Base License and Expansion License.
- New login interface for Control Client.

- Alarm triggered pop-up image displays all the linked cameras' live videos and playback.
- A map can link the resource of any area.
- Generate both parent and child area's BI reports.
- Customize the database backup path.
- Optimize the display of home page and sitemap.
- View live video and playback of the Mobile Surveillance and ANPR module's cameras.
- Store videos by folder when downloading videos.
- Provide quick way to check the exception details in health overview page.
- Notice status to indicate excessive Server's CPU/memory usage.
- Displayed cameras in Playback page are controlled by permissions.
- Choose to show the videos stored on the specified type of storage devices in Playback page.
- Optimize the download function in Playback page.
- Downloaded file size can be up to 2 GB.
- Lock video files stored on the CVR.
- Show service running status and registration status in Service Manager.

Deleted:

- Remove the related functions of mobile surveillance.
- Remove the related functions of entrance/exit and parking lot.
- Remove license plate recognition module.

0303021060713